





This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		ADDED MISSING DIMENSIONS 1.975 & .642, ADDED -3G TO T/N ENGRAVE NOTE, DELETED CHAMFER FROM Ø.750 HOLE PER G.E.	11/16/2009	RJC	RW
1A	14-0216	CH'D TITLEBLOCK WAS RED BARN IS DART. UPDATED 1/2" DRIVE DIMS. CH'D FINISH SPEC WAS MIL-C-81562, TYPE I, CLASS II IS QQ-P-416F, TYPE II, CLASS II. CH'D DIMS WAS .642 IS 2X .642, WAS 4X .386 IS 2X .386. CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS.	11/17/2014	DPD	JAG
2	17-0060	UPDATED TO NEW STANDARDS, CH'D FINISH WAS CAD PLATE YELLOW SPEC MIL-C-81562, TYPE I CLASS I IS ZINC PLATE SPEC ASTM B633 TYPE I, SC2.	3/17/2017	SM	JAG



SECTION A-A

NOTE:
REF. AGUSTA T/N: 3G6205G05951

DART AEROSPACE	
TITLE MAIN ROTOR DAMPER ROD END WRENCH	
DWG NO. RBW6205G05951-3G	REV 2
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 30-35	DIMENSIONS ARE IN INCHES
FINISH ZINC PLATE	.XXX ± .005 FRACTIONS ± 1/8
SPEC ASTM B633 TYPE I SC 2	.XX ± .01 ANGLES ± 5°
DRAWN BY: PERRITT	.X ± .1 SURFACES = 125✓
CHECKED: DD 03/17/2017	1. BREAK ALL SHARP EDGES
OPPS APPR: AA 03/20/2017	.015 x 45° OR .015R
QA APPR: JL 03/29/2017	2. DIMENSIONAL LIMITS APPLY
APPROVED: JAG 04/03/2017	AFTER PLATING
SCALE 1:2	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 1/30/2009	USED ON MODEL
	AW139
	SHEET 1 OF 2

FUNCTION:
USED TO REMOVE/INSTALL THE ROD END
FROM THE MAIN ROTOR DAMPER.

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS
				1	MAIN ROTOR DAMPER ROD END WRENCH	4140/4142	